

This blade emergency escape route sign is designed for surface mount installations. It features a high output rigid LED strip in a compact shell and provides a 30 metre viewing distance.

- ✓ Surface ceiling mount
- ✓ High output LED light source
- ✓ IP20
- ✓ Choice of Legend
- ✓ Option to connect to a wireless self testing system
- ✓ Alternative colour & finish options
- ✓ 0°C to +25°C operating temperature

X-MPC3 Options	
/м	Maintained/Non-maintained
/ST	Self-test
/DALI	DALI (Addressable)
/IP	Wireless Communication
/SL/24	24V AC/DC (central battery)
/SL/50	50V AC/DC (central battery)
/SL/110	110V AC/DC (central battery)
/SL/230	230V AC/DC (static inverter)
/но	50-230V AC/DC hold off relay
/CR	Chrome Finish
/SC	Satin Chrome Finish
/ВК	Black Finish
/CIN	Black Legend

Μ

MAINTAINED

ST

SELF TESTING

Ś

WIRELESS

IP20

NM

NON MAINTAINED

SC

DALI

ADDRESSABLE

 \odot

30m

CBS

CENTRAL BATTERY SYSTEM

Ð

3h

3

YEARS

WARRANTY

Exit Sign LED X-MPC3



Viewing distance: 30 metres



BSEN ISO 7010 legends as standard.

Note: All exit signs are arrow down as standard please specify other direction if required.



FM 58259

* Limited warranty, enquire for full details